

Section-1 IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Identification of the substance/mixture:**Commercial name:** TOLUENE**Chemical name:** TOLUENE C₇H₈**Synonyms:** Benzene methyl, Methacide, Toluole, Methyl benzol, Toluene.**1.2 Use of the substance /mixture:**

For Manufacturing of benzoic acid, benzaldehyde, explosives, dyes, and many other organic compounds; as a solvent for paints, lacquers, gums, resins, in the extraction of various principles from plants, and as gasoline additive.

1.3 MANUFACTURER & SUPPLIER: Reliance Industries Limited**Emergency Coordination Centre contact details:**

Hazira Mfg. Division Village Mora, Dist Surat, Gujarat, India	SSM Office	+91 2612835050/+912612835056
Vadodara Mfg. Division PO Petrochemicals, Dist: Vadodara, Gujrat, India	SSM Office	+91 265-3546525

SSM: Site Shift Manager

Section 2 – HAZARD IDENTIFICATION
--

2.1 Classification of the substance/mixture: Hazard class and category code.**GHS Category:**

Health	Environmental	Physical
Aspiration toxicity category 1 Skin irritation: Category 2 Reproductive/Developmental – Category 2 Specific Target Organ Toxicity (RE) 2	Aquatic Toxicity – Category 1	Flammable – Category 2 Flammable liquid

NA: Not available, RE: Repeated Exposure.

GHS Category table for reference:

Study/hazard statement	Category 1	Category 2	Category 3	Category 4	Category 5
Acute Oral LD50	≤ 5 mg/kg Fatal if swallowed	> 5 ≤ 50 mg/kg Fatal if swallowed	> 50 ≤ 300 mg/kg Toxic if swallowed	> 300 ≤ 2000 mg/kg Harmful if swallowed	> 2000 ≤ 5000 mg/kg May be harmful if swallowed
Acute Dermal LD50	≤ 50 mg/kg Fatal in contact with skin	> 50 ≤ 200 mg/kg Fatal in contact with skin	> 200 ≤ 1000 mg/kg Toxic in contact with skin	> 1000 ≤ 2000 mg/kg Harmful in contact with skin	> 2000 ≤ 5000 mg/kg May be harmful in contact with skin
Acute Inhalation Dust LC50 Gases LC50 Vapours LC50	≤ 0.05 mg/L ≤ 100 ppm/V ≤ 0.5 mg/L Fatal if inhaled	> 0.05 ≤ 0.5 mg/L > 100 ≤ 500 ppm/V > 0.5 ≤ 2.0 mg/L Fatal if inhaled	> 0.5 ≤ 1 mg/L > 500 ≤ 2500 ppm/V > 2.0 ≤ 10 mg/L Toxic if inhaled	> 1.0 ≤ 5 mg/L > 2500 ≤ 20000 ppm/V > 10 ≤ 20 mg/L Harmful if inhaled	See footnote below this table
Flammable Liquids	Flash point < 23 degrees C and initial boiling point ≤ 35 degrees C. Extremely flammable liquid and vapour	Flash point < 23 degrees C and initial boiling point > 35 degrees C. Highly flammable liquid and vapour	Flash point ≥ 23 degrees C ≤ 60 degrees C. Flammable liquid and vapour	Flash point ≥ 60 degrees C ≤ 93 degrees C. Combustible liquid	Not Applicable
<p>Note: Gases concentration are expressed in parts per million per volume (ppmV).</p> <p>NOTE 1: Category 5 is for mixtures which are of relatively low acute toxicity but which under certain circumstances may pose a hazard to vulnerable populations. These mixtures are anticipated to have an oral or dermal LD50 value in the range of 2000-5000 mg/kg bodyweight or equivalent dose for other routes of exposure. In light of animal welfare considerations, testing in animals in Category 5 ranges is discouraged and should only be considered when there is a strong likelihood that results of such testing would have a direct relevance for protecting human health.</p> <p>NOTE 2: These values are designed to be used in the calculation of the ATE for classification of a mixture based on its ingredients and do not represent test results. The values are conservatively set at the lower end of the range of Categories 1 and 2, and at a point approximately 1/10th from the lower end of the range for Categories 3 – 5.</p>					

GHS Category table for reference: Continued

Study/hazard statement	Category 1	Category 2	Category 3
Eye Irritation	Effects on the cornea, iris or conjunctiva that are not expected to reverse or that have not fully reversed within 21 days. Causes severe eye damage.	2A: Effects on the cornea, iris or conjunctiva that fully reverse within 21 days. Causes severe eye irritation. 2B : Effects on the cornea, iris or conjunctiva that fully reverse within 7 days. Causes eye irritation.	Not applicable
Skin Irritation	Destruction of skin tissue, with sub categorization based on exposure of up to 3 minutes (A), 1 hour (B), or 4 hours (C). Causes severe skin burns and eye damage.	Mean value of ≥ 2.3 > 4.0 for erythema / eschar or edema in at least 2 of 3 tested animals from gradings at 24, 48, and 72 hours (or on 3 consecutive days after onset if reactions are delayed); inflammation that persists to end of the (normally 14-day) observation period. Causes skin irritation.	Mean value of ≥ 1.5 < 2.3 for erythema / eschar or edema in at least 2 of 3 tested animals from gradings at 24, 48, and 72 hours (or on 3 consecutive days after onset if reactions are delayed). Causes mild skin irritation.
Environment: Acute Toxicity Category	96 hr LC50 (fish) ≤ 1 mg/L 48 hr EC50 (crustacea) ≤ 1 mg/L, 72/96 hr ErC50 (aquatic plants) ≤ 1 mg/L Very toxic to aquatic life	96 hr LC50 (fish) > 1 ≤ 10 mg/L 48 hr EC50 (crustacea) > 1 ≤ 10 mg/L 72/96 hr ErC50 (aquatic plants) > 1 ≤ 10 mg/L Toxic to aquatic life	96 hr LC50 (fish) > 10 ≤ 100 mg/L 48 hr EC50 (crustacea) > 10 ≤ 100 mg/L 72/96 hr ErC50 (aquatic plants) > 10 ≤ 100 mg/L Harmful to aquatic life
Flammable Aerosol	Extremely flammable aerosol	Flammable aerosol	Not Applicable
Flammable solids	Using the burning rate test, substances or mixtures other than metal powders: (a) wetted zone does not stop fire and (b) burning time < 45 seconds or burning rate > 2.2 mm/second Using the burning rate test, metal powders that have burning time ≤ 5 minutes Flammable solid	Using the burning rate test, substances or mixtures other than metal powders: (a) wetted zone does not stop fire for at least 4 minutes and (b) burning time < 45 seconds or burning rate > 2.2 mm/second Using the burning rate test, metal powders that have burning time > 5 ≤ 10 minutes Flammable solid	Not Applicable

Flammable gases	Gases, which at 20 degrees C and a standard pressure of 101.3 kPA: (a) are ignitable when in a mixture of 13% or less by volume in air; or (b) have a flammable range with air of at least 12 percentage points regardless of the lower flammable limit. Extremely flammable gas	Gases, other than those of category 1, which, at 20 degrees C and a standard pressure of 101.3 kPA, have a flammable range while mixed in air. Flammable gas	Not Applicable
-----------------	---	---	----------------

GHS Label: GHS02: Flame.;GHS08 :Carcinogen**Details of statements:**

Hazard Statements	<p>H225: Highly flammable liquid and vapour.</p> <p>H304: May be fatal if swallowed and enters airways.</p> <p>H315: Causes skin irritation.</p> <p>H336: May cause dizziness or drowsiness.</p> <p>H361: Suspected of damaging fertility or the unborn child.</p> <p>H373: May cause damage to organs through prolonged or repeated exposure</p>
Precautionary Statement Prevention	<p>P203: Obtain, read and follow all safety instructions before use.</p> <p>P210: Keep away from heat/sparks/open flames/hot surfaces No smoking.</p> <p>P 233: Keep container tightly closed.</p> <p>P 240: Ground/bond container and receiving equipment.</p> <p>241: Use explosion-proof electrical/ventilating/lighting/equipment.</p> <p>P 242: Use only non-sparking tools.</p> <p>P 243: Take precautionary measures against static discharge.</p> <p>P 260: Do not breathe dust/fume/gas/mist/vapours/spray.</p> <p>P261: Avoid breathing dust/fumes/mist/vapours/spray.</p> <p>P 264: Wash thoroughly after handling.</p> <p>P 270: Do not eat, drink or smoke when using this product.</p> <p>P280: Wear protective gloves/protective clothing/eye protection/face protection.</p> <p>P271: Use only outdoors or in a well-ventilated area.</p>

Precautionary Statement Response	<p>P301+P316: IF SWALLOWED: Get emergency medical help immediately.</p> <p>P302+P352: IF ON SKIN: wash with plenty of water.</p> <p>P303+P361+P353: IF ON SKIN (or hair): Take off Immediately all contaminated clothing. Rinse SKIN with water [or shower].</p> <p>P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.</p> <p>P318: if exposed or concerned, get medical advice</p> <p>P319: Get medical help if you feel unwell</p> <p>P321: Specific treatment reference to first aid instruction</p> <p>P331: Do NOT induce vomiting.</p> <p>P332+P317: If skin irritation occurs: Get medical help.</p> <p>P362+P364: Take off contaminated clothing and wash it before reuse.</p> <p>P370+P378: In case of fire: Use dry chemical, carbon dioxide to extinguish</p> <p>P314: Get medical advice/attention if you feel unwell.</p> <p>P332+P313: IF SKIN irritation occurs: Get medical advice/attention.</p> <p>P337+P313: IF eye irritation persists: Get medical advice/attention.</p>
Precautionary Statement Storage	<p>P403+P233: Store in a well-ventilated place. Keep container tightly closed</p> <p>P403+P235: Store in a well-ventilated place. Keep cool.</p> <p>P405: Store locked up</p>
Precautionary Statement Disposal	<p>Follow local regulation</p> <p>P501: Dispose of contents/container</p>

Hazard ratings:

NFPA HAZARD CODES	RATINGS SYSTEM
HEALTH: 2	0 = No Hazard
FLAMMABILITY: 3	1 = Slight Hazard
INSTABILITY: 0	2 = Moderate Hazard
	3 = Serious Hazard
	4 = Severe Hazard

Data Reference:

<https://pubchem.ncbi.nlm.nih.gov/compound/Toluene#section=NFPA-Hazard-Classification>

2.2 Information pertaining to particular dangers for human:

Vapors irritate eyes and upper respiratory tract, cause dizziness, headache, anesthesia, respiratory arrest. Liquid irritates eyes and causes drying of skin. If aspirated, causes coughing, gagging, distress, and rapidly developing pulmonary edema. If ingested causes vomiting, griping, diarrhoea, depressed respiration.

2.3 Information pertaining to particular dangers for the environment:

NA.

2.4 Other adverse effects:

Highly flammable and easily ignitable substance. Danger of ignition at normal temperature. Readily evaporates and vapours form with air toxic and explosive mixtures heavier than air. Mixtures keep above ground and after ignition they spread fast into far distances. Ignition possible when exposed to hot surfaces, sparks, naked flames and by electrostatic discharges too. The substance is practically insoluble in water, floats on the water level and forms toxic and explosive mixtures above the water level. Risk of explosion if emptied into drains or released into wastewater.

Attacks rubber and plastics.

Route of entry:

Occupational exposure to toluene can occur through inhalation, dermal contact, and ingestion

Skin Contact	Skin Absorption	Eye Contact	Inhalation	Ingestion
Yes	Yes	Yes	Yes	Yes

DATA REFERENCE:

<https://pubchem.ncbi.nlm.nih.gov/compound/Toluene#section=Exposure-Routes>

Health hazards:

Source	NTP listed?	IARC cancer review group?	OSHA Regulated?
Carcinogenicity	No	No	No

DATA REFERENCE:

[https://pubchem.ncbi.nlm.nih.gov/compound/Toluene#section=International-Agency-for-Research-on-Cancer-\(IARC\)-Classification](https://pubchem.ncbi.nlm.nih.gov/compound/Toluene#section=International-Agency-for-Research-on-Cancer-(IARC)-Classification)

Section 3 – COMPOSITION & INFORMATION ON INGREDIENTS

Ingredients / Hazardous	CAS No.	EC No.	Percentage
Toluene/Yes	108-88-3	203-625-9	> 99.80 %
Benzene/Yes	71-43-2	200-753-7	< 0.05 %

Data reference: <http://ecb.jrc.ec.europa.eu/esis/>

Section 4 – FIRST AID MEASURES
4.1 General advice**IMMEDIATE MEDICAL ATTENTION IS REQUIRED AFTER INHALATION OR AFTER SWALLOWING.**

In case of health troubles or doubts, seek medical advice immediately and show this (Material) Safety Data Sheet.

Ensure activity of vitally important functions until the arrival of the doctor (artificial respiration, inhalation of oxygen, heart massage). If patient is unconscious, or in case of danger of blackout (apsychia), transport patient in a stabilized position. In case of first-degree burns (painful redness), and second-degree burns (painful blisters), cool the affected area with cold running water for a long time. In case of third-degree burns (redness, cracking pale skin, usually without pain), do not cool affected skin, dress the area with sterile dry gauze only.

4.2 Inhalation

Remove patient to fresh air, keep him warm and in order to rest quietly. Avoid walking. Seek medical advice.

SYMPTOMS AND EFFECTS: Cough. Sore throat. Dizziness. Drowsiness. Headache. Nausea. Unconsciousness.

4.3 Skin contact

Immediately take off all contaminated clothing and footwear. Flush effected area with copious quantities of water. Seek medical advice.

SYMPTOMS AND EFFECTS: Dry skin. Redness.

4.4 Eye contact

Immediately flush eyes with clean lukewarm water and continue flushing for at least 15 minutes – keep the eyelids widely apart and flush thoroughly with mild water stream from the inner to the outer Seek medical advice. SYMPTOMS AND EFFECTS: Redness. Pain. .

4.5 Swallowing

If patient is conscious and without convulsion, Do NOT induce vomiting, Never give anything by mouth to an unconscious person, just put patient into a stabilised position. Seek medical advice immediately.

SYMPTOMS AND EFFECTS: Burning sensation. Abdominal pain. Further see Inhalation

Section 5 – FIRE FIGHTING MEASURES

5.1 Suitable extinguishing media

Foam, Dry Chemical Powder, CO₂ and Water in the form of spray.

5.2 Extinguishing media to be avoided

Water in the form of Jet.

5.3 Caution about specific danger in case of fire and fire-fighting procedures

Danger of violent reaction or explosion. Vapours may travel considerable far distances and cause subsequent ignition. Vapours are heavier than air, may cumulate along the ground and in enclosed spaces – danger of explosion. Do not empty into drains. When burning, it emits carbon monoxide, carbon dioxide and irritant fumes. Containers with the substance exposed to excessive heat may explode.

Keep unauthorized personnel out.

Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank.

Use water as a fine spray to control fire and cool adjacent area.

5.4 Special protective equipment for fire-fighters

Section 6 –ACCIDENTAL RELEASE MEASURES

6.1 Person-related safety precautions

Isolate hazard area. Evacuate all unauthorized personnel not participating in rescue operations from the area. Avoid entry into danger area. Remove all sources of ignition. Stop traffic and switch off the motors of the engines. Do not smoke and do not handle with naked flame. Use explosion-proof lamps and non-sparking tools. Avoid contact with the substance. Apply recommended full protective personal equipment. When escaping from the contaminated area, wear mask with cartridge against organic vapours. In case of general average, evacuate personnel from danger area. In places

under the ground level and in enclosed spaces (including drains) risk of explosion and accumulation of toxic vapours.

6.2 Precautions for protection of the environment

Prevent from further leaks of substance. Do not allow substance to enter soil, water and sewage systems. In case of substance discharge to water courses or water containers, inform water consumers immediately, stop service and exploitation of water.

6.3 Recommended methods for cleaning and disposal

Pump off substance safely, soak up residues with compatible porous material and forward for disposal in closed containers. Dispose off under valid legal waste regulations.

Section 7 – HANDLING AND STORAGE

7.1 Information for safe handling

Observe all fire-fighting measures (no smoking, do not handle with naked flame and remove all possible sources of ignition). Take precautionary measures against static discharges. Wear recommended personal protective equipment and observe instructions to prevent possible contact of substance with skin and eyes and inhalation.

Avoid leak to environment.

7.2 Information for storage

Storerooms should meet the requirements for the fire safety of constructions and electrical facilities and should be in conformity with valid regulations. Store in cool, well-ventilated place with effective exhaust, away from heat and all sources of ignition. Do not store together with oxidizing agents.

Take precautionary measures against static discharges. Avoid leak to environment.

7.3 Information for specific use Not applicable.

Section 8 – EXPOSURE CONTROL & PERSONAL PROTECTION

8.1 Occupational Exposure Limits:

Material	Source	Type	ppm	Material
TOLUENE	ACGIH	TWA	20	TOLUENE
	ACGIH	SKIN_DES TWA	NA	
	NIOSH	IDLH	*500	
	OSHA	TLV	200	
	OSHA	CTLV	300	

NA: Data not available

DATA REFERENCE:

[https://pubchem.ncbi.nlm.nih.gov/compound/Toluene#section=Recommended-Exposure-Limit-\(REL\)](https://pubchem.ncbi.nlm.nih.gov/compound/Toluene#section=Recommended-Exposure-Limit-(REL))






Provide adequate ventilation when using the material and follow the principles of good occupational hygiene to control personal exposure.

Recommended determination method in the workplace atmosphere: gas chromatography, detector tube.

8.2 Occupational exposure controls

Collective protection measures: General and local ventilation, effective exhaust. Individual protection measures: Personal protective equipment (PPE) for the protection of eyes, hands and skin corresponding with the performed labour has to be kept at disposition for the employees. In cases, where the workplace exposure control limits cannot be observed with the help of technical equipment or where it is not possible to ensure that the respiratory system exposure does not represent a health hazard for the personnel, adequate respiratory protection have to be kept at disposition. In the case of continuous use of this equipment during constant work, safety breaks have to be scheduled, if the PPE-character requires this. All PPE have to be kept in disposable state and the damaged or contaminated equipment has to be replaced immediately.

RECOMMENDED PERSONAL PROTECTIVE EQUIPMENT (PPE):

HANDS			EYES	BODY		RESPIRATORY	
							

Respiratory protection: If the exposure limit is exceeded and engineering controls are not feasible, wear a supplied air, full-face piece respirator, airline hood, or full-face piece self-contained breathing apparatus. protective mask with canister A (brown coloured, protecting against organic vapours), self-contained breathing apparatus.

Eye protection: Use chemical safety goggles and/or a full face shield where splashing is possible. Maintain eye wash fountain and quick-drench facilities in work area.

Hand protection: Wear gloves of impervious material.

Body protection: Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact. Protective coverall antistatic design recommended, impervious when handling big amounts (nitrile rubber), sealed leather footwear (free from synthetic adhesives)

Hygiene Measures: Wash hands, forearms and face thoroughly after handling. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

8.3 Environmental exposure controls

Proceed in accordance with valid air and water legislative regulations.

Engineering measures: Use only with adequate ventilation. If user operations generate dust, fumes, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Section 9 –PHYSICAL AND CHEMICAL PROPERTIES
--

Appearance	Colourless liquid
Odour	Sweet pungent benzene like
Solubility in water	Insoluble in water , soluble in alcohol
Relative Density (H ₂ O=1)	0.8636
Boiling Point °C	110.6 °C
Melting Point °C	-94.9 °C
Relative Vapour Density (Air=1)	3.1
Flash point °C	4.4°C (Closed cup) 16 °C (open cup)
Auto ignition °C	480 °C
Vapour pressure (mmHg) @ 20 °C	22
Molecular weight	92.14
Explosive limits in air % by volume	LEL 1.1% UEL 7.1%
pH	NA
Viscosity cP @25 °C	0.560
Pour point	NA
Evaporation rate (water=1)	NA
Octanol/water partition coefficient log Kow	2.73
% volatile	NA

NA: NOT AVAILABLE

DATA REFERENCE: <https://pubchem.ncbi.nlm.nih.gov/compound>**Section 10 –CHEMICAL STABILITY AND REACTIVITY INFORMATION****10.1 Conditions to avoid:**

Concentrations within the explosion limits, sources of ignition, high temperature, sun radiation.

10.2 Material to avoid

AIR AND WATER REACTIONS: Highly flammable. Insoluble in water. TOLUENE reacts vigorously with allyl chloride or other alkyl halides even at minus 70° C in the presence of ethyl aluminum dichloride or ethyl aluminum sesquichloride. Explosions have been reported [NFPA 491M 1991]. Incompatible with strong oxidizing agents. When added to a tank of sulfur dichloride, the tank over pressurized and ruptured in a reaction thought to be catalyzed by iron or iron(III) chloride [Chem. Eng. News, 1988, 66(32), 2].

REACTIVE GROUPS: Hydrocarbons, Aromatics

10.3 Hazardous decomposition products

NA

Section 11 –TOXICOLOGICAL INFORMATION
--

11.1 Acute effects

After swallowing possibility of aspiration (passage into the lung) and danger of chemical pneumonia (pulmonary oedema). Product irritates eyes and skin. High vapour concentrations irritate respiratory system and eyes and may lead to fast coma and death.

Acute toxicity data:

Parameter	Route	Species	Values	Exposure period
LC50	Inhalation	Rat	49g/m ³	4 hours
LD50	Oral	Rat	636 mg/Kg	Not applicable
LD50	Dermal	Rabbit	14100 uL/kg	Not applicable

<https://pubchem.ncbi.nlm.nih.gov/compound>

11.2 Repeated dose toxicity: The substance defats the skin, which may cause dryness or cracking. The substance may have effects on the central nervous system. Exposure to the substance may increase noise-induced hearing loss. Animal tests show that this substance possibly causes toxicity to human reproduction or development.

11.3 Sensitisation: May cause skin allergy.

11.4 CMR effects (carcinogenicity, mutagenicity, toxicity for reproduction) Not a CMR.

11.5 Toxicokinetics, metabolism, distribution: NA.

Section 12 –ECOLOGICAL INFORMATION

12.1 Ecotoxicity data:

Parameter	Route	Species	Values	Exposure period	Condition of bioassay
LC50	Inhalation	Bluegill	17 mg/l	24 hours	Not specified
LC50	Inhalation	Daphnia magna (water flea)	313 mg/m ³	48 hours	Not specified

Data Reference: <https://pubchem.ncbi.nlm.nih.gov/compound>

12.2 Mobility: Expected to have high to moderate mobility

12.3 Persistence and degradability: Hydrolysis is not expected to be an important environmental fate process for toluene due to lack of hydrolysable functional groups. Substance is biodegradable.

12.4 Bio accumulative potential: Bio concentration in aquatic organisms is low to moderate.

12.5 Results of PBT assessment Persistence and Degradation: Toluene in air will photo-degrade.

12.6 Other adverse effects

The product is hazardous substance.

Environmental Fate: Toluene is expected to have high mobility in soil. Toluene is expected to biodegrade in soils.

Section 13– DISPOSAL CONSIDERATION

Local Legislation: Disposal should be in accordance with applicable regional, national, and local laws and regulations. This product should not be dumped, spilled, rinsed or washed into sewers or public waterways.

13.1 Recommended disposal methods for the substance / mixture

Product reuse or disposal in accordance with valid waste legislative regulations. If reuse/recycle is not possible, final disposal to be carried out by giving it to approved co-processing/incineration agency.

13.2 Recommended disposal methods for contaminated packaging

Product is transported in tank-vehicles.

Do not drain tank-vehicle cleaning effluent into public sewer, open trench, open ground. Tank-vehicle cleaning effluent to be treated via effluent treatment plant.

13.3 Waste management measures that control exposure of humans and environment

Proceed in accordance with valid health, air and water legislative regulations.

13.4 Waste regulation Follow local regulation.

Section 14– TRANSPORT INFORMATION

International Transport Regulation:

ADR/RID (Road/Rail), IMDG (Sea) and ICAO/IATA (Air)

Proper Shipping Name: TOLUENE
Hazard Class: 3, Flammable Liquid
UN Number: 1294
Packing Group: II
Packaging Instructions: P001/IBC02
Portable tanks: T4/TP1
Emergency Action Code: 3YE

14.2 Special transport precautionary measures

Not applicable.

Section 15– REGULATORY INFORMATION

(M)SDS format on a 16 Section based on guidance provided in:

Indian Regulation:

Manufacture, Storage and Import of Hazardous Chemicals Rule, 1989.
The Factories Act 1948

International Regulations:

European SDS Directive
ANSI MSDS Standard
ISO 11014-1 1994
WHMIS Requirements

United States

Hazard Communication Standard

Canada

Hazardous Products Act and Controlled Products Regulations

Europe

Dangerous Substance and Preparations Directives

Australia

National Model Regulations for the Control of Workplace Hazardous Substances

The Globally Harmonized System of Classification and Labeling of Chemicals endorsed by The UN Economic and Social Council

*RISK PHRASES: R11 Highly flammable, R20 Harmful by inhalation, R38 Irritating to skin, R48 Danger of serious damage to health by prolonged exposure, R63 Possible risk of harm to the unborn child, R65 Harmful: may cause lung damage if swallowed. R67 Vapours may cause drowsiness and dizziness.

*SAFETY PHRASES: S2 Keep out of the reach of children, S36 Wear suitable protective clothing, S37 Wear suitable gloves, S46 If swallowed, seek medical advice immediately and show this container or label, S62 If swallowed, do not induce vomiting; seek medical advice immediately and show this container or label.

*These standard risk and safety phrases for use when interpreting (Material) Safety data Sheets are derived from the European Union Regulation, CHIP Regulations - Chemicals (Hazard Information and Packaging for Supply). They are required to be used in (Materials) Safety Data Sheets to identify potential hazards and offer safe handling advice.

Section 16 – OTHER INFORMATION

Training instructions

Personnel handling the product has to be acquainted demonstrably with its hazardous properties, with health and environmental protection principles related to the product and first aid principles. Termcard details/Reference: Refer Section 14
Local bodies involved: Local District Authority and Local Crisis Group

Sources of data used to compile the (Material) Safety Data Sheet

Data compilation reference: National Institute for Occupational Safety and Health guide to chemical hazards and International Chemical Safety Cards (WHO/IPCS/ILO)

<http://ecb.jrc.ec.europa.eu/esis/index.php?PGM=ein>,

<https://pubchem.ncbi.nlm.nih.gov/compound/Toluene#section=NFPA-Hazard-Classification>

(M)SDS Revision Status:

Date of Revision	Revised Sections	Supersedes
Sep. 01, 2009	Format revised	Feb. 01, 2008
Sep. 01, 2011	Section 2 Health category, 3 Text below table removed, 4 (4.3), and 15 R & S Phrases.	Sep. 01, 2009
Aug. 01, 2013	Section 2 NFPA Hazard statement	Sep. 01, 2011
April 01, 2016	Section 2,12 & 14	Aug. 01, 2013
Jan 31, 2023	Section 2.1,2.2,4.2,4.3,8.1,9,11.1,11.2,13.1,13.2,16	April 01, 2016

This MSDS is issued by Hazira and Vadodara Manufacturing Divisions, Reliance Industries Limited. Contact Details: For any enquiry/comment regarding this Material Safety Data Sheet, kindly contact the ; Hazira SSM office +91 2612835050/+912612835056 or Vadodara SSM Office - +91 265-3546525

Disclaimer:

Reliance Industries Ltd, believes that the information and recommendations contained herein (including data and statements) are accurate as of the date hereof. NO WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE, WARRANTY OF MERCHANTABILITY, OR ANY OTHER WARRANTY, EXPRESSED OR IMPLIED, IS MADE CONCERNING THE INFORMATION PROVIDED HEREIN.

The information provided herein relates only to the specific product designated and may not be applicable where such product is used in combination with any other materials or in any process. Company will not take any warrantee if this product is used in a manner inconsistent with its labeling. Further, since the conditions and methods of use are beyond the control of RIL, expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information.

End of (M)SDS